

型号 Type	额定容量 (5hr) Rated Capacity Ah	最大外形尺寸 Max Over all Dimensions mm				参考质量 Weight(±5%)kg 带液 With Electrolyte
		长L	宽W	槽高H <sub>1</sub>	总高H <sub>2</sub>	
4DB320H	320	77	158	538	564	19.4
5DB400H	400	93				23.5
6DB480H	480	109				27.7
7DB560H	560	125				32
8DB640H	640	141				36.2
9DB720H	720	157				40.3
10DB800H	800	173				44.5
11DB880H*	880	189				48.7
12DB960H*	960	205				53
2DB170H	170	45				158
3DB255H	255	61	15.8			
4DB340H	340	77	20.1			
5DB425H	425	93	24.5			
6DB510H	510	109	28.9			
7DB595H	595	125	33.2			
8DB680H	680	141	37.6			
9DB765H	765	157	41.9			
10DB850H	850	173	46.3			
11DB935H*	935	189	50.7			
12DB1020H*	1020	205	55.1			
2DB180H	180	45	158	577	603	11.9
3DB270H	270	61				16.5
4DB360H	360	77				21.1
5DB450H	450	93				25.7
6DB540H	540	109				30.3
7DB630H	630	125				34.9
8DB720H	720	141				39.4

型号 Type	额定容量 (5hr) Rated Capacity Ah	最大外形尺寸 Max Over all Dimensions mm				参考质量 Weight(±5%)kg 带液 With Electrolyte
		长L	宽W	槽高H <sub>1</sub>	总高H <sub>2</sub>	
9DB810H	810	157	158	577	603	44
10DB900H	900	173				48.6
11DB990H*	990	189				53.3
12DB1080H*	1080	205				57.8
2DB200H	200	45	158	622	648	12.9
3DB300H	300	61				17.9
4DB400H	400	77				23
5DB500H	500	93				28
6DB600H	600	109				33.1
7DB700H	700	125				38.1
8DB800H	800	141				43.2
9DB900H	900	157				48.2
10DB1000H*	1000	173				53.2
11DB1100H*	1100	189				58.2
12DB1200H*	1200	205	63.4			
2DB220H	220	45	158	688	714	14.3
3DB330H	330	61				19.9
4DB440H	440	77				25.5
5DB550H	550	93				31.1
6DB660H	660	109				36.7
7DB770H	770	125				42.2
8DB880H	880	141				47.9
9DB990H	990	157				53.5
10DB1100H*	1100	173				59
11DB1210H*	1210	189				64.7
12DB1320H*	1320	205	70.3			

注：\*号标示为4极柱，H型系列产品电解液密度为  $\rho = (1.290 \pm 0.005) \text{ g/cm}^3 (30^\circ\text{C})$ 。

## 船用铅酸蓄电池

“火炬”牌船用铅酸蓄电池，通过中国船级社型式认证，广泛应用旅游观光船、内河环卫船等内河航运船舶。电池质量可靠，性能稳定，续航能力强，现有三大系列百余种产品，为多家造船主机厂配套使用，D-250 电池先后两次获得中华人民共和国国家最高质量奖。2016 年“火炬”牌船用电池用于 G20 杭州峰会指定专用游船宝石坊，并圆满完成服务任务。



济南大明湖画舫

G20杭州峰会专用游船宝石坊

## GB系列、船用牵引电池型谱

型号 Type	额定容量 Rated Capacity Ah	最大外形尺寸 Max Over all Dimensions mm				参考质量 Weight(±5%)kg 带液 With Electrolyte
		长L	宽W	槽高H <sub>1</sub>	总高H <sub>2</sub>	
D-250	250	204	130	298	329	17.9
D-300	300	204		298	329	19.6
D-330	330	136	180	401	432	22.9
D-395	395	136		401	432	25
D-440	440	174		401	432	30.7
D-515	515	174	158	401	432	32.7
D-380	380	157		314	345	23.1
D-600	600	173		434	465	36.9
9PzS450H*	450	173	198	288	319	26.8
9PzS630*	630	173		401	432	38.4

注：\*号标示为4极柱，电解液密度为  $\rho = (1.290 \pm 0.005) \text{ g/cm}^3 (30^\circ\text{C})$ 。

## 煤矿用特殊型铅酸蓄电池

火炬牌煤矿用特殊型铅酸蓄电池根据中华人民共和国煤炭行业标准 MT 658-2011 研制生产，是供作煤矿电力牵引车辆和与煤矿同级别条件下的其他场所物料搬运设备用防爆电源装置中的直流电源，且产品矿用产品安全标志证书、制造检验合格证齐全。

火炬牌煤矿电池性能稳定、质量可靠、循环寿命长，是乐山宇强、兖矿集团等主机厂的供应商。



## 煤矿防爆电池型谱

型号 Type	额定容量 (5hr) Rated Capacity Ah	最大外形尺寸 Max Over all Dimensions mm				参考质量 Weight(±5%)kg 带液 With Electrolyte	
		长L	宽W	槽高H <sub>1</sub>	总高H <sub>2</sub>		
D330KT (A)	330	136	180	413	454	22.4	
D330KT	330	136		413	454	24.8	
D385KT (A)	385	136		413	454	24.8	
D385KT	385	136		413	454	27.4	
D440KT (A)	440	174		413	454	30.3	
D440KT	440	174		413	454	30.7	
D560KT	560	145		160	541	582	34.9

注：电解液密度为  $\rho = (1.290 \pm 0.005) \text{ g/cm}^3 (30^\circ\text{C})$ 。